


## Cable ducts



### Application

The cable ducts are placed directly onto the extrusions and are secured using either the retaining clips (see page 125) or extrusion nuts available. The duct is easy to open or close any time as it is fitted with a press-on cover. The slotted sides enable cables to be fed in and out at any point.



### Specification

UPVC, light grey

Order data		Order number	
------------	--	--------------	--

Cable ducts		closed	slotted
40mm wide cable duct	standard length	C38-00-00/2000	C38-01-00/2000
	Cut to length	C38-00-02/...	C38-01-02/...
25mm wide cable duct	standard length	B38-00-00/2000	B38-01-00/2000
	Cut to length	B38-00-02/...	B38-01-02/...

Other dimensions on demand

## Aluminium cable ducts 40x40, 40x80, 80x80

### Application

The cable ducts can be placed directly on to the extrusions and secured using screws and threaded plates / extrusion nuts. The duct is easy to open or close any time as it is fitted with a press-on cover.




### Description

Size 40x40mm, 40x80 and 80x80

### Specification

Anodised aluminium

### Aluminium cable duct with cover



#### Dimension

HxB	b	h	Slot
40x40	30.8	27.8	1
40x80	70.5	27.8	2
80x80	70.5	66.5	2

Order data	Order number
Aluminium cable duct 40x40 (B=40, H=40) incl. cover	
Standard length 6000 mm	C38-11-00/6000
Cut to length	C38-11-02-02/...

Order data	Order number
Aluminium cable duct 40x80 (B=80, H=40) incl. cover	
Standard length 6000 mm	C38-21-00/6000
Cut to length	C38-21-02-02/...

Order data	Order number
Aluminium cable duct 80x80 (B=80, H=80) incl. cover	
Standard length 6000 mm	C38-31-00/6000
Cut to length	C38-31-02-02/...

## Front cover



### Application

A range of different covers and designs are available for the aluminium cable ducts 40x40, 40x80 and 80x80 to cover the open cross-sections. Available with or without outlet holes for possible cable passage.


Specification: Zinc-coated steel

Parts supplied:


Front cover with adjusting screws



Design with  $\text{\O} 40 \times 40$



Design with U-shape 40x80



Closed design 80x80


Design 40x40	Order number	Design 40x80	Order number	Design 80x80	Order number
closed	C38-14	closed	C38-24	closed	C38-34
U-shape 24x27mm (Uxb)	C38-15	U-shape 26x60mm (Uxb)	C38-25	U-shape 60x66mm (Uxb)	C38-35
1x $\text{\O} 20.6$	C38-18	3x $\text{\O} 16$	C38-26	4x $\text{\O} 16$	C38-36
		2x $\text{\O} 20.6$	C38-28	4x $\text{\O} 20.6$	C38-38

## Cable duct connector

### Application

The connectors are used to extend the cable ducts and create a 90° mitred connection (other angles on request). 2 connectors are required for the aluminium cable ducts 40x80 and 80x80. The threaded pins used to fix the ducts are included with the parts supplied.

Specification: zinc-coated steel  
Adjusting screws: M5



Connector, straight



Connector, 90°, other angles on request

Order data	Order number
Connector, 90°	C38-90
Connector, straight	C38-91

## Covering cap for front cover

### Application

The covering cap is used to cover unnecessary openings on the front plates.




Plastic, black

Order data	Order number
Ø 16	C38-46
Ø 20	C38-47

## Cable passage to front cover

### Application


This edge protection is used at places where cables need to be fed through the cable duct on the front face. Available for the relevant holes in the front covers.



Plastic, black

Order data	Order number
D= 16    Ø 12.7	C38-56
D= 20    Ø 16	C38-57

### Retaining clips




**Application**

The quarter turn retaining clips allow the easy fixing of either cable ducts or thin sheet material onto the extrusions Base 50, 40 and 30.

**Specification**


PA-GF, black




Order data	Order number
------------	--------------

Retaining clips A = 5.5	AC38-20
Retaining clips A = 3.5	B38-20

### «Velcro» Cable ties



### tie wrap «base»




**Application**

This universal cable tie is made from a combination of Velcro material and a retaining clip. The Velcro can be cut to length with scissors. The quarter turn retaining the clip ensures easy fixing to the extrusions Base 50,40 and 30.

On the tie-wrap-base you can fix standard tie wraps. Fix with a M5-screw

**Specification**


Clips: glass-filled Polyamide (PA-GF) black  
 Ribbon: Velcro black  
 Tie wrap Base: PA black



Order data	Order number
------------	--------------

Cable ties «Velcro»	Extrusion base 50/40	30
	B50-50	B50-53
Tie wrap «Base»	50/40/30/20	
	B50-55	

### Installation rings



**Application**

Installation rings are ideal for holding cables and pipes in place, and as tool holders. The rings can be fixed into the 8 mm extrusion slot using an M4 screw. They are held in place without twisting in the slot. There are two different diameters of rings available to cover the various possible applications.

**Specification**

PA-GF, black



Order data	Order number
------------	--------------

	D	
Installation ring	Ø 18	B50-20
Installation ring	Ø 33	B50-30